

Metamark MDP-H

100 micron High Tack Vinyl

METAMARK

The Materials Company

Product Description

MDP-H has a high tack adhesive to solve the problem of adhesion onto smooth low energy surfaces, such as Polypropylene, Polyethylene and ABS, as well as for durable graphics on extreme sports equipment. The 100 micron film makes it suitable for print and cut labels and easy application.

Handling and Printing Guidelines

- Ensure that the material has reached room temperature and a relative humidity of 50% before printing.
- Do not handle the face film directly and ensure it is free from dust and static.
- Suitable for use on Solvent, Eco Solvent, Latex and U.V. inkjet printers. Always perform a test print first.
- Ensure that the correct profiles and heater settings are used. Most profiles are available for download from www.metamark.co.uk.

Overlaminating

- Overlamination is recommended to prevent abrasion and to extend colour fastness.
- Allow the inks to cure before overlaminating, this is usually 24-48 hours.
- The matched laminate for MDP-H is MetaGuard 305 or 302. For all other laminates the user should determine suitability.

Application

- Allow the inks to cure before cutting or overlaminating, usually 24-48 hours. Perform cut path as separate operation to avoid edge curl.
- Not recommended for heavily textured surfaces. The user should determine suitability of substrate, refer to the web site.
- Refer to www.metamark.co.uk for application guidelines.

Face Film

Face Film:	Monomeric calendered PVC
Gauge:	100 micron nominal
Tensile Strength	60N/25mm MD / 52N/25mm TD nom.
Elongation at break	180% MD nominal

Adhesive

Type	High-tack perm. Solvent-based acrylic
Weight	23gsm nominal
Adhesion LDPE	20 min 24 hour
	5N/25mm nominal 15 N/25mm nominal
Adhesion Steel	20 min 24 hour
	22 N/25mm nominal 28 N/25mm nominal
Adhesion Glass	20 min 24 hour
	22 N/25mm nominal 28 N/25mm nominal
Perceived tack	High
Application temperature	+5°C to +60°C
Service temperature	-5°C to +100°C

Finishes

Finishes Available	MDP-H-200	White Gloss
--------------------	-----------	-------------

Roll Presentation

Roll sizes and net weights	685mm x 50m 1370mm x 50m	10kg 20kg
Presentation Face film outwards, on a 76mm core.		

Durability

Shelf Life	1 year
Fire Rating	Self-extinguishing. The fire rating is a function of the substrate.
External weathering	4 years. This refers to the unprinted vinyl when installed. Refer to ink manufacturer for durability of the finished product.

Release Liner

Weight	140 gsm nominal
Type	Kraft paper

Warranty: Metamark (UK) Limited warrants to its customers that graphics produced using Metamark Digital Media will remain in good condition without excessive fading or colour degradation for the specified life time of the ink used, when correctly stored, printed and applied in accordance with procedures outlined in the technical literature. If within the specified years of normal use Metamark DigitalVinyl becomes ineffective for its intended use, then Metamark will provide sufficient material to produce a new replacement marking, and will at its own discretion, contribute an allowance in additional material towards the costs involved in replacing the graphics. In all cases, the converter is held fully responsible for storing, processing and applying the unconverted materials in accordance with Metamark's technical specifications. Metamark (UK) Limited will not be liable for any indirect or consequential loss or damage, and will not provide any allowance against improper usage, application accident, negligence, chemical damage or improper repair. **Please Note:** The above data is given in good faith to provide an indication of the performance of the product. Purchasers should consider the suitability of each product for its intended use and the purchaser assumes all risks in connection with such use. Seller shall not be liable for damages in excess of the purchase price of the product nor for incidental or consequential loss.

Metamark (UK) Limited