

Metamark MD-SC

Static Cling (Self-Cling Window Film)

Product Description

Metamark Digital Static Cling is a 170 micron self-cling film available in white or clear. It can be applied to glass or metal and typically used to produce labels and promotional window decals. Once printed and contour cut, the printed surface can be applied to the glass and backing then removed. The white film provides opacity for solvent inks which are generally translucent. It can be applied to glass or metal and typically used to produce labels and promotional window decals.

Material Handling

- Ensure that the material has reached room temperature and a relative humidity of 50% before printing.
- Do not handle the face film directly and ensure it is free from dust and static.

Printing Guidelines

- Suitable for use on Solvent and Eco Solvent inkjet printers. Always perform a test print first.
- Ensure that the correct profiles and heater settings are used. Most profiles are available for download from www.metamark.co.uk.
- Print with correct orientation with white version of the static cling, or it may be reversed with clear version, which also allows the clear pvc to be backed up with a solid white.
- Allow a border to prevent edge curl.
- The product does not become touch dry instantly. Avoid use of a take up roller and do not stack prints until fully cured.

Application

- Allow the inks to cure before cutting flush to the print, and before application, this is usually 24-48 hours.
- Ensure the glass is clean from grease and dirt. Do not use silicon based cleaning products.
- Take care applying to cold glass as initial adhesion will be reduced.
- Once the decal is cut, apply direct to the window from the backing liner before removal.
- Note: If the printed face is applied directly to the window it may leave some print residue which can be cleaned after.

Face Film

Face Film: 170 micron PVC

Finishes

Finishes Available	MD-SC-100	White Gloss
	MD-SC-105	Clear Gloss

Adhesion

Adhesive	None
Service Temperature:	-20°C (-5°F) to 50°C (122°F)
Application temperature:	+10°C (+50°F) Min
Adhesion:	Both sides adhere securely on clean glass

Roll Presentation

Roll sizes	760mm x 25m
	1370mm x 25m
Presentation	Face film outwards, on a 76mm core.

Release Liner

Gauge	140gsm
Type	Kraft

Durability

Shelf Life	1 year
External weathering	2 Years Exterior, 5 Years Interior
	This refers to the unprinted vinyl when installed. Refer to ink manufacturer for durability of the finished product.

Warranty: Metamark (UK) Limited warrants to its customers that graphics produced using Metamark Digital Media will remain in good condition without excessive fading or colour degradation for the specified life time of the ink used, when correctly stored, printed and applied in accordance with procedures outlined in the technical literature. If within the specified years of normal use Metamark DigitalVinyl becomes ineffective for its intended use, then Metamark will provide sufficient material to produce a new replacement marking, and will at its own discretion, contribute an allowance in additional material towards the costs involved in replacing the graphics. In all cases, the converter is held fully responsible for storing, processing and applying the unconverted materials in accordance with Metamark's technical specifications. Metamark (UK) Limited will not be liable for any indirect or consequential loss or damage, and will not provide any allowance against improper usage, application accident, negligence, chemical damage or improper repair. **Please Note:** The above data is given in good faith to provide an indication of the performance of the product. Purchasers should consider the suitability of each product for its intended use and the purchaser assumes all risks in connection with such use. Seller shall not be liable for damages in excess of the purchase price of the product nor for incidental or consequential loss.

Metamark (UK) Limited